

Technical data

Dry moly spray

The logo for MOLYSLIP, featuring the brand name in a bold, italicized, sans-serif font with a registered trademark symbol, set against a red rectangular background.

Molybdenum disulphide dry film lubricant

Description

MOLYSLIP DRY MOLY SPRAY is a high performance, resin bonded, dry film lubricant based on molybdenum disulphide. When applied to metal substrates the molybdenum disulphide forms a resilient, low friction film that protects against wear and corrosion. DRY MOLY SPRAY reduces metal pick-up and galling during component assembly and dry start up conditions and where traditional “wet” lubricants either can’t be used or do not provide adequate lubrication.

DRY MOLY SPRAY can be used in a wide variety of operating conditions – the applied film will operate between -50°C and $+450^{\circ}\text{C}$ without flaking or cracking. Unlike oils and greases the dry nature of the film will not attract dirt and dust and it is resistant to water wash-off making it ideal for use in extreme environments.

Features and benefits

- Low co-efficient of friction film provides outstanding protection against wear
- Wide operating temperature range of -50°C to $+450^{\circ}\text{C}$
- Does not attract dirt and dust
- Touch dry in under 1 minute allows components to be in service quickly
- Prevents pick-up and galling

Instructions for use

Shake well, hold can upright and spray from a distance of approximately 15-30cm.

Coat the metal surface evenly and allow to dry.

After spraying invert the can and spray until clear (failure to do this can result in valve blockage).

If required burnish the surface with a lint free cloth after a minimum of 1 minute drying time.

Packaging

400ml aerosol

Technical data

Dry moly spray

The logo for MOLYSLIP, featuring the brand name in a bold, italicized, sans-serif font with a registered trademark symbol, set against a red rectangular background.

Technical data (typical values)

Property	Result
Appearance of applied film	Grey/black dry film
Propellant	LPG
Co-efficient of friction	0.08
Effective temperature range	-50°C up to +450°C

The product information in this publication is based on knowledge and experience at the time of printing. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.
Issue date 06-17

Molyslip Atlantic Limited, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester, M44 5EG, UK
Tel: +44 (0)161 804 4700 Fax: +44 (0)161 804 4701 enquiries@molyslip.co.uk www.molyslip.co.uk

Company registration number: 02664511; Company registered in England VAT registration number GB578295191