Technical data



SLIPCLEAN RD

Zero residue, rapid drying solvent cleaner

Description

MOLYSLIP SLIPCLEAN RD is a highly effective, zero residue, rapid drying cleaner and degreaser based on high purity hydrocarbons and alcohols. The product is designed for the safe and effective removal of a wide range of industrial soils/contaminants including oil, grease, carbon deposits, inks and semi-cured adhesives.

MOLYSLIP SLIPCLEAN RD is compatible with most commonly encountered industrial substrates, patch testing should however be carried out when using on sensitive materials. The high purity and fast evaporation rate leaves surfaces clean and residue free. In addition to multiple industrial uses MOLYSLIP SLIPCLEAN RD is also NSF K1 registered and suitable for use on food processing equipment.

Features and benefits

- NSF K1 Registered (167241)
- Highly effective cleaning
- Rapid drying
- Zero residue
- Suitable for use on food processing equipment

Instructions for use

Hold upright and spray component to be cleaned liberally from a distance of 15-30cm (6 - 12inches). Do not spray near naked flames or incandescent material. Use in a well-ventilated area.

Storage

MOLYSLIP SLIPCLEAN RD should be stored in original, unopened packaging, out of direct sunlight at temperatures between 5°C and 35°C. The most up to date shelf life information for Molyslip products can be found on the certificate of analysis issued at the time of manufacture.

Packaging and product code

Code	Pack	
M475004	400 mL aerosol	

Metalube Group Ltd, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester, M44 5EG, UK Tel: +44 (0)161 775 7771 enquiries@molyslip.co.uk www.molyslip.co.uk Company registration number: 2263118; Company registered in England VAT registration number GB108244927

Technical data



SLIPCLEAN RD

Zero residue, rapid drying solvent cleaner

Technical data

Property	Test method	Result
Appearance	-	Colourless liquid
Odour	-	Mild, characteristic
Propellant	-	Hydrocarbon
Solvent type	-	Hydrocarbon / Alcohol
Flash point (of solvents)	PMCC	<0°C

Note: these values are typical only and do not constitute a specification

Limited warranty information

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective and fully satisfactory for the intended end use. We accept no liability for any loss and/or damage arising from a failure to store our products in accordance with the information contained in this technical sheet.

Metalube Group's sole warranty is that our products will meet their quality control specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

To the fullest extent permitted by applicable law, Metalube Group specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability. Metalube Group disclaims liability for any incidental or consequential damages.

Metalube Group Ltd, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester, M44 5EG, UK

Tel: +44 (0)161 775 7771 enquiries@molyslip.co.uk www.molyslip.co.uk Company registration number: 2263118; Company registered in England VAT registration number GB108244927